



PRIMER 100

Product Name

Flex-C-Ment™ Primer 100

Size: 5 Gallon Pail

Manufacturer

Flex-C-Ment Products div. of CAG Inc.

1205 Palestine Road Picayune, MS 39466

Ph. 888-515-2132

Fax 601-798-1069

www.flex-c-ment.com

Description

Flex-C-Ment's™ Primer is designed to permanently adhere new concrete to existing sound surfaces. It adheres new concrete to adverse surfaces such as painted, sealed, glazed or damp surfaces. It is white in appearance and dries clear. Once dried, it is non-flammable, resistant to alkali attack from masonry and cement materials and VOC compliant. Flex-C-Ment™ Primer may be used to interior or exterior applications and may be applied with a brush or roller.

Uses

Flex-C-Ment's™ Primer bonds cement materials to concrete, plaster, masonry, drywall, wood and various adverse surface conditions. Flex-C-Ment's™ Primer is designed for bonding surfaces including overlays, recapping existing concrete, leveling/ correcting uneven or defaced concrete, over painted or sealed surfaces.

Installation

- Check for loose scaly areas such as dirt, loose paint, dust, loose concrete, etc. All loose particles must be removed. Use a good degreaser to remove grease. Mildew (or algae) can usually be removed by using bleach and a wire brush in a small area. Larger areas should be cleaned first with bleach, and then washed with a pressure sprayer.
- Can be applied with either brush or roller. Apply just like a thick coat of paint.



Flex-C-Ment™ Primer 100

- Install overlay as soon as Flex-C-Ment™ Primer 100 has been applied. Apply overlay while Primer 100 is still wet.
- Surface does not have to be totally dry when applying Flex-C-Ment™ Primer. No standing water should be present.
- Tools should be cleaned immediately after use.

PRECAUTIONS

- Do not use or apply to frozen or frost-covered surfaces. Do not apply when ambient air or surface temperature is below freezing or expected to fall below 40°F within forty-eight hours.
- Keep Flex-C-Ment™ Primer from freezing.

Manufacturer's Warranty

The data, statements and recommendations herein are the results of tests we believe to be accurate and reliable, but do not constitute a warranty, expressed nor implied.

Installer assumes all liability for the use of this product and must use their own information and testing to evaluate its proper use for the desired result.

It shall be the sole responsibility of the manufacturer/seller to replace that portion of this product which proves defective during the three year period following its purchase, and neither shall be liable to buyer or to any third person for injury, direct or indirect loss, or damage related to this product.

Statements and recommendations are binding upon the manufacturer/seller only when in writing and properly signed by an officer of the manufacturer.